



INSTALLING ROLLER BUNKS

P/N 27700 (4 FT) P/N 27710 (5 FT)

**HARDWARE REQUIRED FOR ADJUSTABLE MOUNTING:
(NO HARDWARE IS INCLUDED)**

- 4—P/N 10003GA Adjustable Roller Bunk Mounting Brackets
- 4—3/8"-16 x 1" Hex head bolts with washers & nuts to attach Roller Bunk Mounting Brackets to Roller Bunks
- 8—Bolts, washers & nuts to attach mounting brackets to trailer frame

TOOLS REQUIRED

- 2—9/16" Wrenches

A. With Adjustable Mounting Brackets - P/N 10003GA - Requires 4

1. Position and attach (4) bracket assemblies to trailer cross members at desired width and height locations.
2. Place roller bunks over swivel bracket assemblies and adjust lengthwise to fit. Roller bunks have several universal mounting holes, but drilling additional holes may be necessary to match your trailer's cross member locations.
3. Attach roller bunks to swivel bracket assemblies with 3/8"-16 x 1" hex head bolts. Place washer next to bolt head before inserting through roller bunk channel. Fasten with 3/8"-16 nylon lock nuts.
4. Adjust roller bunks to angle of your boat and secure swivel bracket assemblies.
5. Adjust height again if necessary.

Roller Bunks may be mounted directly on top of flat (horizontal) wooden bunk boards or mounted directly to trailer cross members.

CAPACITY = 1500 LBS. PER PAIR OF BUNKS (4 FT. OR 5 FT.)